

## IF-CB/DM

### CobraNet<sup>®</sup> Interface Card for DM-3200/DM-4800



The IF-CB/DM interface card for the Tascam DM-3200 and DM-4800 digital consoles allows connection to CobraNet<sup>®</sup> audio networks over CAT-5 cable. The card transfers up to 16 channels of digital audio to and from CobraNet devices. The DM-3200 can accommodate one IF-CB/DM (Slot 1), while up to two cards can be used in the DM-4800 (Slots 1 and 3) for a total of 32 audio channels in and out. This card helps reduce cost, labor and time in live applications and when installing large-scale systems.

#### Main Features

- 16 input / 16 output audio interface to CobraNet<sup>®</sup> networks for DM-3200 and DM-4800 consoles
- Up to 100 m signal transmission over CAT-5 cable interface
- 48 kHz sample rate at 24-bit resolution
- Redundant network switches to secondary line if problems occur
- Selectable signal latency: 1.33 ms, 2.67 ms or 5.33 ms
- Less than 1 ns jitter
- CobraNet Discovery application included for monitoring and maintenance of CobraNet network interface
- CobraCAD application included for checking network system design

#### Specifications

--

Design and specifications subject to change without notice.

Last modified: 2010-10-07 14:39:20 UTC