

RC-HS32PD

Flash Start Remote Control for HS series



The RC-HS32PD is a remote control unit for the HS-4000 and HS-2000 broadcast recorders. It offers flash start with 32 dedicated keys and further control through a colour TFT touch screen interface that mirrors the recorder. Each key has a 64x32 dot matrix colour LCD for file name display. Two 100-mm faders include a microswitch for fader start/stop, a 0-dB level lock to help prevent overload and on-air signal indication, and a speaker and headphones output are provided for monitoring. The RC-HC32PD can be used in single or dual deck mode and connects to the recorder using CAT6 cable for long-distance runs.

Features at a glance

- Flash start or fader start/stop control for HS-4000 and HS-2000
- Colour TFT touch screen interface for full control of the recorder
- 32 flash start keys with 64 x 32 dot matrix colour LCD for file name display
- Single Deck mode (32 keys x 3 pages) or Dual Deck mode (16 keys x 6 pages)
- Two operation modes:
 - Flash start: Press key to start playing the take immediately
 - Standby: While a take is playing, press key to reserve the take as the next playback take to be started immediately after the current take is finished
- Two 100-mm faders with fader start/stop capability and 0-dB lock
- Monitor speaker and headphones output for monitoring
- CAT6 remote connection with recorder
-

Specifications

Analogue audio outputs

Speaker (mono)

Maximum output power

1 W

PHONES connector

6.3-mm standard stereo jack

Maximum output power

45 mW + 45 mW (THD+N 0.1% or less, into 32 Ω)

Power supply and other specifications

Power voltage

DC 41V (provided by the main unit)

Power consumption

8 W

Dimensions (W x H x D)

429 mm x 99 mm x 232 mm

Weight

4.3 kg

Operating temperature range

5–35 °C

Design and specifications subject to change without notice.

Page last modified: 2020-08-20 15:36:38 UTC

TEAC Europe GmbH

Bahnstrasse 12

65205 Wiesbaden

Germany

Tel: +49 611 7158-0

Share this page:

© 2003–2021 TEAC Europe GmbH · TEAC Corporation · All rights reserved.